



DVD MECHLESS

DV712

INSTALLATION/OWNER'S MANUAL

DVD Multimedia Receiver with Bluetooth® featuring a 7" Touch Screen Display















Safety Notes: (Only DVD Receiver)

The DVD video display of the in-dash unit will not operate while the vehicle is moving. This is a safety feature to prevent driver distraction. In-dash DVD video functions will only operate when vehicle is in Park and the parking brake is engaged. It is illegal in most states for the driver to view video while the vehicle is in motion.

Copyright Notes This product incorporates copyright protection technology that is protected by method claims of certain U.S. patents and other intellectual property rights owned by Macrovision Corporation and other rights owners. Use of this copyright protection technology must be authorized by Macrovision Corporation, and is intended for home and other limited viewing uses only unless otherwise authorized by Macrovision Corporation. Reverse engineering or disassembly is prohibited. The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. SD Logo is a trademark of SD-3C, LLC. Other trademarks and trade names are those of their respective owners.

Table of Contents	Page
Warning Statement	. 3
Safety Information/Precautions	. 4
Preparation/Mounting	. 5
Wiring Diagram	. 6
Control Locations.	. 7
Remote Preparation	. 8
General Operation	9-11
AM/FM Tuner Operation	. 12
CD/USB/SD Card Operation	. 13
Media Compatibility	14-16
DVD Operation	. 17-18
Bluetooth Operation	19-20
Auxiliary Inputs/Rear Camera Operation	. 21
SWC Input Operation	. 22
Specifications	. 23
Warranty	24
Troubleshooting	. 25



A WARNING A

Upon installation of this Monitor/DVD player ("unit") into a vehicle, the driver of the vehicle must not operate this unit by watching videos or playing video games while driving. Failure to follow this instruction could lead to driver distraction which could result in serious injury or death to the vehicle's occupants or persons outside the vehicle and/or property damage.

Several states prohibit the installation of monitors/DVD players if the screen is visible from the driver's seat. If you reside in a jurisdiction which has enacted such a law, this unit must not be installed so that the screen is visible from the driver's seat. When installing this unit in the front console/dashboard, the unit must be positioned so that it is facing the front passenger seat only. Failure to follow this instruction could lead to driver distraction which could result in serious injury or death to the vehicle's occupants or persons outside the vehicle and/or property damage.

This unit is designed so that it may be operated only when the vehicle is in "Park" and the parking brake is fully engaged. To this end, this unit includes a parking brake lock-out feature which prohibits the unit from operating if the vehicle is not in "Park" and/or the parking brake is not fully engaged. When installing this unit, the installer must connect the parking brake detect wire to the parking brake mechanism in order to make the parking brake lock-out feature operable. DO NOT simply ground the parking brake detect wire to a metal portion of the vehicle. Failure to properly install the parking brake lock-out feature could lead to driver distraction which could result in serious injury or death to the driver's occupants or persons outside the vehicle and/or property damage.

Once the parking brake lock-out feature is installed, the owner/user must not attempt to disrupt/neutralize the parking brake lock-out feature by (a) partially engaging the parking brake and/or (b) purchasing/using any device or unit designed to send necessary brake signals to the unit. Failure to follow these instructions could lead to driver distraction which could result in serious injury or death to the driver's occupants or persons outside the vehicle and/or property damage.

When operating this unit, keep the unit's volume level low enough so that the vehicle's occupants can hear traffic-related sounds such as police and emergency vehicles. Failure to follow this instruction could lead to driver distraction which could result in serious injury or death to the vehicle's occupants or persons outside the vehicle and/or property damage.

* Note

The above video Content is for DVD Receiver Only.



▲ Safety Information

Please read all instructions carefully before attempting to install or operate.

Due to its technical nature, it is highly recommended that your DUAL DV712 is installed by a professional installer or an authorized dealer. This product is only for use in vehicles with 12VDC negative ground only.

To prevent damage or injury:

- Make sure to ground the unit securely to the vehicle chassis ground.
- . Do not remove the top or bottom covers of the unit.
- . Do not install the unit in a spot exposed to direct sunlight or excessive heat or the possibility of water splashing.
- . Do not subject the unit to excessive shock.
- When replacing a fuse, only use a new one with the prescribed rating. Using a fuse with the wrong rating may
 cause the unit to malfunction.
- To prevent short circuits when replacing a fuse, disconnect the wiring harness first.
- · Use only the provided hardware and wire harness.
- You cannot view video while the vehicle is moving. Find a safe place to park and engage the parking brake.
- If you experience problems during installation, consult your nearest DUAL dealer.
- If the unit malfunctions, reset the unit as described on page 10 first. If the problem still persists, consult your nearest DUAL dealer or call tech assistance @ 1-866-382-5476.
- To clean the monitor, wipe only with a dry silicone cloth or soft cloth. Do not use a stiff cloth, or volatile solvents such as paint thinner and alcohol. They can scratch the surface of the panel and/or remove the printing.
- When the temperature of the unit falls (as in winter), the liquid crystal inside the screen will become darker than usual. Normal brightness will return after using the monitor for a while.
- When extending the ignition, battery or ground cables, make sure to use automotive-grade cables or other cables with an area of 0.75mm (AWG 18) or more to prevent voltage drops.
- Do not touch the liquid crystal fluid if the LCD is damaged or broken. The liquid crystal fluid may be hazardous
 to your health or fatal. If the liquid crystal fluid from the LCD contacts your body or clothing, wash it off with soap
 immediately.

FCC Compliance

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- · Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- · Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.




Preparation

Before You Start

- Disconnect negative battery terminal. Consult a qualified technician for instructions.
- Avoid installing the unit where it would be subject to high temperatures, such as from direct sunlight, or where it
 would be subject to dust, dirt or excessive vibration.

Getting Started


- Insert the supplied keys into the slots as shown, and slide the unit out of the mounting sleeve.
- Install mounting sleeve into opening, bending tabs to secure.
- Connect wiring harness as shown on page 6. Consult a qualified technician if you are unsure.
- Certain vehicles may require an installation kit and/or wiring harness adapter (sold separately).
- Reconnect negative battery terminal, and test for correct operation.
- Snap trim ring into place (if required).
- Slide unit into mounting sleeve to secure.



TYPICAL FRONT-LOAD DIN MOUNTING METHOD



Wiring Diagram - Inputs/Outputs



Note:

When replacing a fuse, make sure to use the correct type and amperage. Using an incorrect fuse could cause damage. The unit uses (1) 10 amp ATM mini style fuse located power connector.

Wiring Notes:

Subwoofer output


The Subwoofer preamp audio output (black jacket with green RCA) is active in all audio modes.

Rear camera input

A rear view camera (not included) can be used with the Camera input.




Control Locations



- 1 Eject
- (4) Microphone
- (5) Tune/Track Down
 - 8 Band
- 7 Mute/End call
- 10 Release
- 11 Mode

- 2 Auxiliary Input (3) USB Port
- VOL Up/Down/Talk
- 9 Open / Power
 - 12 Tune/Track Up



- Power
- Mode
- Play / Pause
- Mute
- Title
- Subtitle
- Setup
- Angle
- Eject
- Volume Up
- Zoom
- (12) Select / Talk
- (13) Seek Up / Next Track
- Volume Down

- (15) Audio
- (16) Go To /*
- (17) Loudness / End Call
- Number Keys
- (19) Root
- (20) OSD (On Screen Display)
- (21) Local / Random
- Seek Down / Previous Track
- AS/PS / Repeat
- (24) Stereo
- (25) Stop
- Enter
- Band



Remote Control Preparation


Remove battery insulation tape.



Notes:

- The remote control uses one 3 volt Lithium CR2025 battery. Remove the battery if the remote will not be used for a month or longer.
- Remove and dispose of battery properly.
- Do not store battery with metallic objects or materials.

To insert or replace the battery, remove the battery holder.




Remove the battery from the battery holder.




Install the new battery. Make sure to keep the (+) side up.



Insert the battery holder .







General Operation

Installing the Faceplate

Align the faceplate with the front of the unit, then snap in place beginning with the left side.

Power On/Off

Momentarily press \circ to turn the unit on or off.

Volume

Rotate the volume knob to increase or decrease the volume level.

Mute

Momentarily press MUTE to silence the audio. Momentarily press MUTE again to return to the previously selected volume. Rotating the volume knob while the volume is muted will also cancel the mute function.

Mode

Press MODE to step through all available input modes: Radio, Disc (which includes DVD and CD playback), microSD Card, AV In, iPod, Bluetooth Phone, Bluetooth Audio, Auxiliary Input, Rear Camera and Settings. Modes of operation are indicated on the display and/or the monitor. Optional iPod device and microSD Card, must be connected/inserted to appear in the mode selection string.

Auxiliary Input

Connect external audio/video devices to the 3.5mm auxiliary input on the front panel.

microSD Card

Insert an microSD Card into the microSD Card slot (located behind the faceplate) to play MP3 files.

Opening the LCD

Press OPEN to open or close the LCD screen.

Screen Angle

Press UP▲ or DOWN ▼ to adjust the screen angle up or down.

Main Menu

Press the Home Icon at the top left of each mode to switch to the main menu screen below.



DV712 OPERATION



Setup Menu

From the Main Menu screen, press Settings in the bottom right corner to access the Setup Menu and select from the following categories: General, Audio, Video and Bluetooth.



General:

- OSD Language Select English Only.
- Wallpaper Select between three available wallpaper options.
- Panel Adust Select to calibrate the touch screen.
- Radio Area Select your current geographic area: Europe, USA, South America, Russia and Asia.
- Time Setting -Adjust the current time (hours and minutes) and choose between a 12-hour and 24-hour clock.
- Beep -Select to turn the audible beep On or Off.
- · Camera -Select to turn the rear camera On or Off.
- Version -Select to view information about the unit.
- Restore Default Select to restore the unit to default settings.

Audio:

- Sound Effect -Select to access the three sound effect sub-menus.
 - -EQ -Select from any preset equalization curve (Classic, Rock, Pop, Jazz, Beat, Flat) or use custom settings (User).
 - -Subwoofer -Select the desired Subwoofer frequency and volume.
 - -Loudness -Turn the Loudness setting On or Off.
 - -Loudness Cut off Frequency -Select the desired frequency as a cutoff for the Loudness setting.

Video:

- Aspect Ratio -Select the desired aspect ratio: 4:3PS, 4:3LB or 16:9.
- Adjust -Select to adjust levels of Brghtness, Contrast, Hue, Saturation and Sharpness.
- Panel -Select to choose backlightsettings: 10s, 20s, 30s or Off.

Bluetooth:

- Auto Connect -Turn auto connect feature On or Off.
- Auto Answer Turn auto answer feature On or Off.

General Operation

Touch Screen Controls

The touch screen controls on the bottom of each screen allow direct access to important features during any mode of operation.



- Standby (1) Press to dim the display or put the unit in Stanby mode.
 - Eject (2) Press to eject the disc.
- Audio 3 Press to adjust audio options such as EQ, Surround Sound and Balance/Fader.
- Settings (4) Press to access the settings menu.



AM/FM Tuner Operation



Radio Operation

Select the Radio icon from the Main Menu screen.

Main Menu (1)

Press to return to Main Menu screen.

Current Mode Indicator (2)

Displays current mode of operation.

Tune Frequency Down (3)

Press << to tune radio to a lower frequency. Press < to tune the unit down one step at a time.

Band (4)

Press between 2 AM and 3 FM bands.

Local / Distance (5)

Press to toggle between Local and Distance tuning.

Tune Frequency Up (6)

Press >> to tune radio to a higher frequency. Press > to tune the unit up one step at a time.

AS/PS (7)

Press to scan presets and listen to the first 10 seconds of each. Press again to stop scanning and listen to the station. Press and hold to automatically find and store the strongest stations as presets.

Stereo (8)


Press to toggle between Stereo and Mono tuning.

Preset Stations (9)

Press and hold to set the current station in that preset spot. Press momentarily to recall the desired preset and begin playback.



CD/USB/microSD Card Operation



CD/USB or SD Operation

To play audio files from a disc or MP3 files from a disc, USB device or SD card, insert disc or device and playback will begin automatically. To return to disc, USB or microSD Card playback from another mode of operation, select the corresponding icon from the Main Menu.

- Disc Playback Insert disc into the slot, and playback will begin automatically.
- USB Playback Insert a USB device into the USB slot on the side of the unit
- microSD Card Playback Insert microSD Card into the microSD Card slot on the top of the unit. When inserting an SD card, the label should face up.

Main Menu 1 Press to return to Main Menu screen.

Current Mode Indicator 2 | Displays current mode of operation.

Repeat ③ Press to select a repeat option: Repeat 1, Repeat Folder or Repeat Off.

Random (4) Press to enable or disable random playback.

Previous File / Track (5) Press to go back to the previous file or track.

Play / Pause 6 Press to pause or resume playback.


Next File / Track 7 | Press to advance to the next file or track.

Folder Access (8) Press to access all folders on device.



Media Compatibility - CD/DVD

				-
File Type				MP3
	Level 1, Level 2		Level 2	✓
	IS09660	Level 3		Х
	IS09660	IS09660 JOLIET	Playback	✓
File System			Filename	32 bytes
		ROMEO -	Playback	Х
	Other Extensions		Filename	Х
	LATERISIONS	Appl	e ISO	Х
File	.mj	p3/.MP3/.Mp3/.mP3		4
Extension		.rmp/.m4a		Х
		MPEG 1		✓
MPEG Format	MPEG 2			✓
Format	MPEG 2.5			✓
	MPEG 1			32/44.1/48kHz
Sampling Frequency	MPEG 2			12/16/22.05/24kHz
requestey	MPEG 2.5			8/11.025/12kHz
	MPEG 1			32 ~ 320kbps
Bitrate	MPEG 2			8 ~ 160kbps
	MPEG 2.5			8 ~ 160kbps
Other Information	Directory Depth			Unlimited
	File Name Length			32 bytes
	Total File Number			2000 files
	Total Folder Number			200 folders
	File Number via Folder			2000 files
	ver.1.x			✓
	MP3 ID3 TAG		:2.x	✓
	Title, Artist, Album			✓



Media Compatibility - USB/microSD Card

	MP3		
File System	FAT	FAT 12	Х
	FAI	FAT 16/FAT 32	✓
File	.mp3/.MP3/.Mp3/.mP3		✓
Extension	.rmp/.m4a		Х
	MPEG 1		✓
MPEG Format	MPEG 2		✓
Tormat		MPEG 2.5	✓
	MPEG 1		32/44.1/48kHz
Sampling Frequency		MPEG 2	12/16/22.05/24kHz
requestoy		MPEG 2.5	8/11.025/12kHz
	MPEG 1		32 ~ 320kbps
Bitrate		MPEG 2	8 ~ 160kbps
	MPEG 2.5		8 ~ 160kbps
	Directory Depth		Unlimited
	File Name Length		32 bytes
Other Information	Total File Number		2000 files
	Total Folder Number		200 folders
	File Number via Folder		2000 files
		ver.1.x	✓
	MP3 ID3 TAG	ver.2.x	✓
		Title, Artist, Album	✓

DV712 OPERATION



Media Compatibility

Media Compatibility

The following types of discs/files are compatible:

- CD-DA, CD-ROM (ISO), CD-R, CD-RW
- DVD Video, DVD+R/RW, DVD-R/RW

The following types of discs/files are not compatible:

- WMA files that are protected by DRM (Digital Rights Management)
- · WMA lossless format
- Discs recorded with Track At Once or packet writing
- MP3 PR0 format, MP3 playlists
- RMP format
- WAV format
- WMV format
- AAC, protected AAC, M4A format, M4V.

Some recordable DVD's and CD's may be incompatible with this unit, depending on media type and recording method.

Playback Order

MP3 playback sequence begins in the root folder of the disc, USB flash drive or microSD Card. Any empty folders or folders that do not include MP3/JPG files are skipped.

Compatible Recording Formats

IS09660 standards:

- Maximum nested folder depth is 8 (including the root folder).
- Valid characters for folder/file names are letters A-Z (all caps), numbers 0-9, and "_" (underscore). Some characters may not be displayed correctly, depending on the character type.
- This device can play back discs in Joliet and other standards that conform to ISO9660. MP3 written in the formats other than the above may not play and/or their file names or folder names may not be displayed properly.


Notes

Some files may not play or be displayed correctly, depending on sampling rates and bit rates.

For best results, use the following settings when ripping MP3 files: 128kbps or higher constant bit rate 44.1kHz or higher sampling frequency



DVD Operation



Inserting a Disc

Insert disc into the slot, and playback will begin automatically. Submenus may have to be pressed to access the DVD content. Read the directions of your specific DVD disc for other features.

Eiecting the Disc

Press

to eiect the disc.

Touchscreen Controls

Press anywhere on the LCD to display touch screen controls.

Main Menu (1)

Press to return to Main Menu screen.

Elapsed Time (2)

Displays elapsed time and time remaining on the DVD.

Repeat (3)

Press to select from the following repeat options: Repeat Chapter, Repeat Title, Repeat All or Repeat Off

Previous Chapter (4)

Press to return to the previous chapter on the DVD.

Play / Pause (5)

Press to play or pause DVD playback.

Next Chapter (6)

Press to advance to the next chapter.

Random (7)

Press Random to play chapters in random order or Random Off to play disc in order.

Audio (8)

Audio Language Setting



DVD Operation



Screen Setup 9 | Screen Color Setting


Zoom (10) Zoom in and out on an image

Subtitle (1) Press to access subtitle options.

Audio (12) Press to adjust Audio options.

Monitor On/Off (13) Put the monitor into standby mode.

Setting (14) | Setup Menu Direct Access



Bluetooth Operation



Preparation

Before you can use a Bluetooth device, it must be paired and connected. Make sure that Bluetooth is activated on your device before you begin the pairing process.

Pairing a New Device

The unit broadcasts the pairing signal constantly when no devices are currently connected. Complete the pairing sequence from your Bluetooth device. Refer to the owner's manual for your device for more details. The device name is "DV712".

The Bluetooth passcode is "0000". The unit can be in any mode of

The Bluetooth passcode is "0000". The unit can be in any mode of operation when pairing is performed. On certain phones, pairing may need to be done more than once.

Connecting a Paired Device Most Bluetooth devices support the auto-connect feature and will connect automatically if the device is in range when the unit is powered-on. If your device was previously paired but does not connect, enter the Bluetooth setup menu and ensure that Auto Connect is On.

Bluetooth Phone

To access the phone, select Bluetooth Phone from the Main Menu or press the phone icon from any operational mode.

Main Menu (1)

Press to return to the Main Menu screen.

Current Mode Indicator (2)

Displays current mode of operation.

Phone Keypad (3)

Use the phone keypad to dial the desired phone number. Alternately, numbers can be dialed directly from the phone.

Bluetooth Phone 4

Press to access Bluetooth phone.

Bluetooth Music (5)

Press to access Bluetooth music.

_

Press to view a list of available devices.

Available Devices 6

Talk (7)

Press to connect a call.

End Call (8)

Press to end a call.



Bluetooth Operation





- Standby (9) Press to put the monitor into standby mode.
 - Eject 10 Press to eject the disc.
 - Audio (1) Press to adjust Audio options.
- Settings (12) Press to access the Settings menu.
- Bluetooth Music (13) Press to access Bluetooth Music (from Phone mode).
- Previous File / Track (14) Press to go back to the previous file or track.
 - Play / Pause (15) Press to pause or resume playback.
 - Next File/Track (16) Press to advance to the next file or track.
 - Bluetooth Phone (17) Press to access Bluetooth Phone (from Music mode).

Front 3.5mm Aux Input & Rear RCA A/V Input

Auxiliary Input

Connect an optional audio source into the 3.5mm (front panel) input.

Select auxiliary input from the Main Menu to listen to audio.

Adjust volume on the external audio source as needed (if connected to the headphone output of the device).

Using AV Input

Connect an optional audio/video source to the rear auxiliary input (Red/White/ Yellow RCA connectors). Refer to page 6 for details.

Select AV Input from the Main Menu to listen to audio.

Engage parking brake to watch video.

Rear Camera Operation - (Optional)

Using Rear Camera

Connect an optional rear camera to the Camera Input (Black RCA connector). Refer to the wiring diagram for details.

Manual selection - Touch CAMERA icon from the Main Menu or from any operational mode (when enabled) to select camera mode. Touch the top left area on the screen to exit camera mode.

Note: The manual mode is for dedicated cameras that are ALWAYS on while driving, it is not meant for cameras that are connected to the vehicle's reverse light.

Auto Selection

The unit will automatically select camera mode when connected to the reverse lamp circuitry.

Note: The external video output is not active when using the rear camera input.



SWC Input Operation

The built-in SWC Interface is compatible with PAC steering wheel control modules. The PAC SWI-RC is recommended. A third-party adapter must be used in order for the XDVD276BT to be compatible with any steering wheel controls.

The following controls are available for most vehicles:

1. Volume Up (+)	4. Preset (+)	7. Seek/Track Up (+)	10. BT Talk
2. Volume Down (-)	5. Preset (-)	8. Seek/Track Down (-)	11. BT End
3. Mute	6. Mode	9. Band	


Note:

Not all OE steering wheel functions may be supported by the XDVD276BT.

PAC SWI-RC Installation Hints

- 1. Set "Radio Select Switch". Set the SWI-RC to position 7 "Pioneer/Other/Sony".
- 2. Programming Use the Pioneer/Sony/Other radio function mapping order for Dual branded head units.
- When programming the SWI-RC, if a function is not supported (or not desired), then the function MUST be skipped as per the PAC SWI-RC instructions.
- The SWC function MUST be programmed in the correct order per the PAC SWI-RC radio function mapping order instructions.

Function Order	Function Mapping	SWI-RC (3.3VDC Reference)		
		Center Pin (Ring) Voltage (Function Select)	Tip Pin Voltage	
1	Volume +	H 5.0v	2.07	
2	Volume -	H 5.0v	2.32	
3	Mute	H 5.0v	1.01	
4	Preset +	L 0.0v	1.54	
5	Preset -	L 0.0v	1.81	
6	Source	H 5.0v	0.6	
7	Seek + / Track +	H 5.0v	1.54	
8	Seek - / Track -	H 5.0v	1.81	
9	Band	H 5.0v	2.73	
10	BT Talk	L 0.0v	0.6	
10	BT End	L 0.0v	1.01	



Specifications

Disc | Frequency response: 20Hz-20kHz

Channel separation @ 1kHz: >80dB

D/A converter: 24 Bit

FM Tuner Tuning range: 87.5MHz-107.9MHz

Usable sensitivity: 10dBf 50dB quieting sensitivity: 20dBf Stereo separation @ 1kHz: 38dB Frequency response: 30Hz-13kHz

AM Tuner Tuning range: 530kHz-1710kHz

Usable sensitivity: 24uV

Frequency response: 30Hz-2.3kHz

Front USB | Compatibility: High Speed USB 2.0

USB Class: Mass storage class

SD | Compatibility: microSDHC memory card & microSDHC memory card

Monitor Panel size: 7" diagonal measurement

View angle (up/down/left/right): 50/70/70/70

Resolution: 800 (H) x 480 (V) Brightness (cd/m²): 250 Contrast ratio: 500:1 Pixels: 1.152.000

General

Speaker output impedance: 4 ohms Line output voltage: 1 volt RMS Line output impedance: 200 ohms

Chassis dimensions: 7" x 7" x 2" (W x D x H)

Design and specifications subject to change without notice.



CEA-2006 Power Standard Specifications (reference: 14.4VDC +/- 0.2V, 20Hz~20kHz)

Power Output: 16 Watts RMS x 4 channels at 4 ohms and \leq 1% THD+N Signal to Noise Ratio: 80dBA (reference: 1 watt into 4 ohms)

DV712 OPERATION



Limited One Year Warranty

This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

Dual Electronics Corp. warrants this product to the original purchaser to be free from defects in material and workmanship for a period of one year from the date of the original purchase.

Dual Electronics Corp. agrees, at our option, during the warranty period, to repair any defect in material or workmanship or to furnish an equal new, renewed or comparable product (whichever is deemed necessary) in exchange without charges, subject to verification of the defect or malfunction and proof of the date of purchase. Subsequent replacement products are warranted for the balance of the original warranty period.

Who is covered? This warranty is extended to the original retail purchaser for products purchased from an authorized Dual dealer and used in the U.S.A.

What is covered? This warranty covers all defects in material and workmanship in this product. The following are not covered: software, installation/removal costs, damage resulting from accident, misuse, abuse, neglect, product modification, improper installation, incorrect line voltage, unauthorized repair or failure to follow instructions supplied with the product, or damage occurring during return shipment of the product. Specific license conditions and copyright notices for the software can be found via www.dualav.com.

What to do?

- Before you call for service, check the troubleshooting guide in your owner's manual.
 A slight adjustment of any custom controls may save you a service call.
- If you require service during the warranty period, you must carefully pack the product (preferably in the original package) and ship it by prepaid transportation with a copy of the original receipt from the retailer to an authorized service center.
- Please describe your problem in writing and include your name, a return UPS shipping address (P.O. Box not acceptable), and a daytime phone number with your shipment.
- 4. For more information and for the location of the nearest authorized service center please contact us by one of the following methods:
 - Call us toll-free at 1-866-382-5476
 - E-mail us at cs@dualav.com

Exclusion of Certain Damages: This warranty is exclusive and in lieu of any and all other warranties, expressed or implied, including without limitation the implied warranties of merchantability and fitness for a particular purpose and any obligation, liability, right, claim or remedy in contract or tort, whether or not arising from the company's negligence, actual or imputed. No person or representative is authorized to assume for the company any other liability in connection with the sale of this product. In no event shall the company be liable for indirect, incidental or consequential damages.



Troubleshooting

General			
Problem	Cause	Action	
Unit will not turn on	Yellow wire not connected or incorrect voltage Red wire not connected or incorrect voltage	Check connections for proper voltage (11~16VDC)	
(no power)	Black wire not connected	Check connection to ground	
	Fuse blown	Replace fuse(s)	
Hait has names	Speaker wires not connected	Check connections at speakers	
Unit has power (but no sound)	One or more speaker wires touching each other or touching chassis ground	Insulate all bare speaker wires from each other and chassis ground	
Unit blows fuse(s)	Yellow or red wire touching chassis ground	Check for pinched wire	
	Speaker wires touching chassis ground	Check for pinched wire	
	Incorrect fuse rating	Use fuses with correct rating	
Unit has audio (but no video)	Parking brake safety circuit not connected Parking brake not applied	Check connections at parking brake Apply parking brake as described on page 26	
No video display (when in reverse)	Reverse circuit not connected Vehicle is not in reverse	Check connections at reverse lamp Select reverse gear	
DVD does not start playback	Physical defect in media Wrong region	Check media for scratches Use discs labeled "Region 1" or "All" only	
IR remote does not work	Dead battery	Replace battery	
Excessive skipping	Unit is not mounted correctly	Check mounting sleeve	
	Physical defect in media	Check media for scratches	
Disc Region Incorrect appears on display	Region code error	Use discs labeled "Region 1" or "All" only	

For Your Records	Please keep your original sales receipt and be prepared to provide this receipt in the event you require service, as your original receipt is considered the best proof o purchase and indicates the date you purchased your Dual product.		
	Dealer Name Dealer Phone Purchase Date		
Register Your Product	Register your product online at www.dualav.com.		

DV712 OPERATION



Notes



Dual Electronics Corp. Toll Free: 1-866-382-5476 Monday-Friday, 9AM-5PM EST

www.dualav.com ©2022 Dual Electronics Corp. All rights reserved. NSC0822-V01